

SHARLU SUPER FORMULA 2000

SAE Viscosity Grade : 20W/40, 20W/50, 10W, 30, 40, 50

Performance Level : CC/SC
MIL-L-2104B

Product Description **Sharlu Super Formula** is formulated with high quality paraffinic base oils & excellent additive package. It is suitable for all diesel/gasoline engines operating in mild severe conditions.

Main Benefits

- This is high viscosity index oil
- It has good level of detergency & dispersancy
- Wear protection, rust protection
- Multi fleet oil for both diesel and gasoline engine.
- It gives good start

Application **Sharlu Super Formula** is recommended for use in diesel and petrol engine in commercial light duty vehicles, vans, passengers cars, stationary engines and material handling machines operating in mild service conditions.

Physical Characteristics	Test Method	Typical Value					
		20W/40	20W/50	10W	30	40	50
Specific Gravity 60/60 °F	ASTM D-4052	0.908	0.891	0.879	0.884	0.894	0.899
Viscosity, cSt	ASTM D-445						
@ 40 °C cSt		194.10	159.63	33.41	104.36	160.12	208.98
@ 100 °C cSt		17.50	17.50	5.50	11.60	15.50	18.5
Viscosity Index	ASTM D-2270	97	120	100	98	98	98
Pour Point, °C	ASTM D-97	-6	-18	-12	-9	-6	-6
Flash Point COC, °C	ASTM D-92	264	240	218	226	248	258
TBN mgm KOH/gm	ASTM D-2896	4.90	4.00	3.42	3.42	3.42	3.42