

SHARLU HYDROFLUID AW

ISO Viscosity Grade: 32, 46, 68, 100

This is a premium quality anti-wear hydraulic oil. It is made from solvent refined high VI base stock combined with anti-wear, defoamant additives and rust inhibitors. Sharlu Hydrofluid AW is recommended for all mobile and stationary hydraulic systems operating under severe conditions. It can also be used in circulation, splash and ring oil lubrication systems and compressors where recommended.

Main Benefits

- Cleaner servo valves, less chances for sticking.
- Multi-metal compatibility under wet and dry conditions.
- Superior filterability increases filter life.

Sharlu Hydrofluid AW meets and exceeds the requirements Sperry Vickers, Denison HF-0, Racine, Sundstrand, Lucas & Din 51524 Part II.

Typical Characteristics

ISO Grade	S. Gravity ASTM D-4052 @ 60/60 °F	K. Viscosity, cSt ASTM D-445		Visc. Index ASTM D-2270	Flash Point ASTM D-92 COC, °C	Pour Point ASTM D-97 °C
		40 °C	100 °C			
32	0.874	31.30	5.36	104	216	-36
46	0.877	44.10	6.66	103	222	-27
68	0.881	64.10	8.43	101	236	-27
100	0.885	99.50	11.40	101	240	-24