

SHARLU EXTRA SP MOTOR OIL

SAE Viscosity Grade : 20W/50

Performance Level : SF/CD

CCMC G2/D1, MIL-L-46152B

Product Description **Sharlu Extra SP Motor Oil** is a fine blend of high quality base stocks and carefully selected additive package. The effective properties of dispersants / detergents, anti-wear and anti-corrosion ensure excellent engine lubrication and protection. The special stay-in grade viscosity index improver enhances the oil performance and maintains oil viscosity over a range of operating temperatures.

Sharlu Extra SP Motor Oil is designed to perform under elevated temperature and the most severe driving conditions.

Main Benefits

- All year round useability
- Superior engine performance due to freedom from ring sticking and reduced deposits
- Better fuel economy
- Low maintenance cost through better performance

Application **Sharlu Extra SP Motor Oil** is recommended for use in gasoline/diesel fuelled naturally aspirated or turbo charged automotive engines and passenger cars, taxis, vans and light trucks.

Physical Characteristics	Test Method	Typical Value
SAE Grade		20W/50
Specific Gravity 60/60 °F	ASTM D-4052	0.8920
Kinematic Viscosity, cSt	ASTM D-445	
@ 40 °C cSt		153.50
@ 100 °C cSt		17.50
Viscosity Index	ASTM D-2270	125
Pour Point, °C	ASTM D-97	-24
Flash Point COC, °C	ASTM D-92	238
TBN mgm KOH/gm	ASTM D-2896	6.20